

## DS-PDWL-E-WB



- Water-proof design for multiple use applications
- Fully remote configurable through App
- Multiple enrollment method and easy installation design
- Frequency hopping against jamming for reliable transmission
- External probe included



## ▪ Specification

| Model                      |                                   | DS-PDWL-E-WB  |
|----------------------------|-----------------------------------|---|
| Feature                    | Digital Processing                | Support   |
|                            | Tamper Protection                 | Front, Rear   |
|                            | Environment Temperature Indicator | Support   |
|                            | Signal Strength Indicator         | Support   |
| Interface                  | LED Indicator                     | Blue (Alarm)  |
| Transmission               | Transmission Technology           | Tri-X Wireless  |
|                            | Transmission Method               | Two-Way RF Wireless                                       |
|                            | Transmission Frequency            | 433MHz  |
|                            | Transmission Security             | AES-128 Encryption  |
|                            | Transmission Range(Free Space)    | 1Km   |
|                            | Frequency Hopping                 | Support   |
|                            | Enrolling Method                  | Power up, Remote ID,QR Code                               |
| Electrical Characteristics | Standard Battery Life             | 3 years in work status (being triggered 20 times per day) |
|                            | Power Supply                      | Battery Powered   |
|                            | Battery Type                      | CR2450 x 1  |
|                            | Typical Voltage                   | 3V  |
| General                    | Operation Temperature             | -10 °C to 55 °C (14 °F to 131 °F)                         |
|                            | Storage Temperature               | -20 °C to 60 °C (-4 °F to 140 °F)                         |
|                            | Operation Humidity                | 10% to 90%  |
|                            | IP Rate                           | IP66  |
|                            | Dimension(Wx HxD)                 | 62.4mm × 62.4mm × 14.6mm                                  |
|                            | Weight                            | 85.5g   |

|  |                      |                                       |
|--|----------------------|---------------------------------------|
|  | Mounting Method      | Wall, Surface                         |
|  | Application Scenario | Indoor standalone/with included probe |

**▪ Available Model**

DS-PDWL-E-WB

Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com